

**Product Data** 

# **Castrol EDGE Professional LongLife III 5W-30**

Boosted with TITANIUM FST™ - Strength for Maximum Performance

## **Description**

Castrol EDGE Professional, boosted with TITANIUM FST™, provides outstanding oil strength for today's engines that work harder, with higher pressures than ever before.

Castrol EDGE is our strongest and most advanced range of engine oils. Its TITANIUM FST™ doubles its film strength, preventing oil film breakdown and reducing friction.

Castrol EDGE Professional with TITANIUM FST™: helping your engine perform at its best.

Castrol EDGE Professional is now certified CO2 neutral according to the highest global standards. Engineered with micro filtration in order to meet Castrol Professional's new quality standard and verified using Castrol's new Optical Particle Measurement System to guarantee product quality.

## **Application**

Castrol EDGE Professional LongLife III 5W-30 is suitable for use in automotive gasoline and diesel engines where the manufacturer recommends an ACEA C3 5W-30 lubricant.

Castrol EDGE Professional LongLife III 5W-30 is recommended and approved for use in OEM vehicles that require VW 504 00 / 507 00, Porsche C30 specifications.

## **Advantages**

Castrol EDGE Professional LongLife III 5W-30 gives you the confidence to demand maximum engine performance from VW vehicles engineered with variable long drain technology, requiring lower viscosity, stronger oils for longer drain intervals.

Castrol EDGE Professional LongLife III 5W-30:

- Maximises short and long term engine performance
- Reduces engine deposits to help maximise engine response
- · Delivers complete protection across a variety of engine speeds, conditions and temperatures
- Sustains maximum performance even when under pressure
- Independently proven to improve engine efficiency
- Delivers unsurpassed levels of protection across a variety of driving conditions and temperatures

## **Typical Characteristics**

| Name                      | Method     | Units      | Castrol EDGE Professional Longlife III 5W-30 |
|---------------------------|------------|------------|--|
| Density @ 15C, Relative   | ASTM D4052 | g/ml       | 0.851  |
| Viscosity, CCS -30C (5W)  | ASTM D5293 | mPa.s (cP) | 5700   |
| Viscosity, Kinematic 40C  | ASTM D445  | mm²/s      | 66   |
| Viscosity Index           | ASTM D2270 | None       | 173  |
| Pour Point                | ASTM D97   | °C         | -39  |
| Flash Point, PMCC         | ASTM D93   | °C         | 196  |
| Ash, Sulphated            | ASTM D874  | % wt       | 0.75   |
| Viscosity, Kinematic 100C | ASTM D445  | mm²/s      | 11.6   |

#### **Product Performance Claims**

ACEA C3 Porsche C30 VW 504 00/507 00

### **Storage**

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional LongLife III 5W-30 29 Apr 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk