

Granville FS-ECO 5W/20

1 Litre, 5 Litre, 20 Litre & 205 Litre



Product Description

FS-ECO 5W/20 is a fully synthetic engine oil formulated for the latest intelligent Eco engines including stop/start technology. The carefully selected base stocks and synthetic additives give this multigrade engine oil high levels of engine component protection as well as being fuel efficient.

Recommended for use by Granville for the following manufacturer's specifications

Ford: WSS-M2C948-B & WSS-M2C948-A

ACEA: C5

ILSAC: GF-5

STJLR: .03.5004

API: SN/CF



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0772	5020618007722
5 Litre	0773	5020618007739
20 Litre	0777	5020618007777
205 Litre	0775	5020618007753

Product Benefits

- *Long drain service intervals, subject to manufacturers recommendations
- *Keeps engine clean
- *Protects components from wear and corrosion
- *Excellent cold start capabilities

Product Usage

For use where the engine manufacturer recommends this specification and viscosity oil.

Directions for Use

Use as per manufacturers recommendations.

Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil



Granville FS-ECO 5W/20

1 Litre, 5 Litre, 20 Litre & 205 Litre



Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	6.9	<9.3	7.8
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	4567
Total Base Number	ASTM D2896	mg KOH/g	8		9.795
HTHS Viscosity	ASTM D4683	mPa.s	2.6	<2.9	
NOACK Volatility	ASTM D5800	%		13	11
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			43.523
Viscosity Index	ASTM D2270				150.55
Density	ASTM D792	@ 15°C			0.849
Pour Point	ASTM D97	°C		-35	-39

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

