



Granville FS-NX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Granville FS-NX 0W/30 is a highly advanced fully synthetic engine oil formulated to give the most advanced protection and performance under all operating conditions giving increased fuel economy and extended service intervals. FS-NX is suitable for use in petrol and diesel engines with and without turbos where the manufacturer recommends this grade and specification of lubricant.

Note: Not suitable for engines with 2 or 3 turbochargers.

Recommended for use by Granville for the following manufacturer's specifications

ACEA: C2

BMW: LL-12 FE

Product Benefits

- *Increased fuel economy
- *Extended service intervals

Product Usage

Not suitable for engines with 2 or 3 turbochargers

Directions for Use

Use as per manufacturer's recommendations

Storage Instructions

Store sealed in a cool, dry place out of the reach of children.

Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	1059	5020618010593
5 Litre	1060	5020618010609
20 Litre	1061	5020618010616
199 Litre	1064	5020618010647





Granville FS-NX 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	9.94
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Total Base Number	ASTM D2896	mg KOH/g	7		7.98
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		11	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			54.84
Density	ASTM D792	@ 15°C			0.845

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

