



## Granville FS-VC 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Granville FS-VC 0W/30 is a fully synthetic engine oil formulated to meet the performance demands of modern petrol and diesel engines. FS-VC 0W/30 is a blend of the very latest in base oil and additive technology, designed for extended drain performance, especially suited for modern Volvo engines.

### Recommended for use by Granville for the following manufacturer's specifications

ACEA: A5/B5

API: SL/CF

Volvo: VCC 95200377



\* Image for illustrative purposes only.

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

For engines where this specification and viscosity of lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Keep upright and sealed in a cool, dry place out of the reach of children.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water

Size	Part No	Barcode
1 Litre	0522	5020618005223
5 Litre	0523	5020618005230
20 Litre	0516	5020618005162
199 Litre	0521	5020618005216





## Granville FS-VC 0W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	9.99
Total Base Number	ASTM D2896	mg KOH/g	8		10.62
HTHS Viscosity	ASTM D4683	mPa.s	2.9	<3.5	
NOACK Volatility	ASTM D5800	%		13	
Cold Cranking Viscosity	ASTM D4684	mPa.s		6200	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			53.87
Density	ASTM D792	@ 15°C			0.845
Pour Point	ASTM D97	°C		-40	

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

