



## Granville Hypalube C2 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Granville Hypalube C2 5W/30 is a new generation, fully synthetic multi-grade engine oil formulated to meet the performance demands of low emission engines which combine high performance, fuel efficiency and emission control. Manufactured to a Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C2 oil. It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used. NOTE: This oil is NOT suitable for Vehicles that require Low Speed Pre-ignition (LSPI) capabilities. Suitable for vehicle up to 2017.



\* Image for illustrative purposes only.

### Recommended for use by Granville for the following manufacturer's specifications

ACEA: C2  
PSA: B71 2290 (<2017)  
API: SN/CF

Size	Part No	Barcode
1 Litre	0704	5020618007043
5 Litre	0705	5020618007050
20 Litre	0709	5020618007098
199 Litre	0708	5020618007081

### Product Benefits

- \* Mid SAPS (Sulphated ash, phosphorous and sulphur content) formulation
- \* Fully Synthetic

### Product Usage

Use where recommended by the engine manufacturer

### Directions for Use

Use as required by the engine manufacturer

### Storage Instructions

Store sealed and upright in a cool dry place out of the reach of children

### Shelf Life

5 years form date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Biodiesel	:	Nil





## Granville Hypalube C2 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.36
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		7.98
Pour Point	ASTM D97	°c		-35	
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		11	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			60.49
Density	ASTM D792	@ 15°C			0.852

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

