



Granville Hypalube C4 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Product Description

Granville Hypalube C4 5W/30 is an advanced, fully synthetic low viscosity engine oil formulated to meet the performance demands required by manufacturers who recommend an oil that combines high performance, fuel efficiency and emission control. Manufactured to a Low SAPS (Sulphated ash, phosphorous and sulphur content) formulation. Recommended for all engine types where the manufacturer specifies a C4 oil. It is imperative that the correct oil is used as costly repairs will be required if the wrong specification of lubricant is used.

Recommended for use by Granville for the following manufacturer's specifications

ACEA: C4
MB: 226.51
Renault: RN0720

Product Benefits

- * Low SAPS (Sulphated ash, phosphorous and sulphur content) formulation
- * Fully Synthetic

Product Usage

Use where recommended by the engine manufacturer

Directions for Use

Use as required by the engine manufacturer

Storage Instructions

Store sealed and pright in a cool dry place out of the reach of children

Shelf Life

5 years from date of manufacture

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water



* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0814	5020618008149
5 Litre	0815	5020618008156
20 Litre	0819	5020618008194
199 Litre	0818	5020618008187





Granville Hypalube C4 FS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm ² /s	9.3	<12.5	11.572
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	6		8.46
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		11	
Kinematic Viscosity at 40°C	ASTM D445	mm ² /s			71.05
Density	ASTM D792	@ 15°C			0.851

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

