



## Granville Hypalube LX Mineral 10W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Granville Hypalube LX 10W/30 is a superior mineral engine oil, formulated to increase engine protection during cold start up thereby reducing engine wear. Hypalube 10W/30 is a low viscosity engine oil that offers improved fuel economy and outstanding engine cleanliness.

### Recommended for use by Granville for the following manufacturer's specifications

API: SL/CF  
ACEA: A2/B2 & E2  
MB: 229.1  
VW: 505.00  
Ford: WSS-M2C909-A



\* Image for illustrative purposes only.

Size	Part No	Barcode
1 Litre	0083	5020618000839
5 Litre	0081	5020618000815
20 Litre	0091	5020618000914
199 Litre	0094	5020618000945

### Product Benefits

- \* Ensures lubricant performance
- \* Excellent high & low temperature performance
- \* Suitable for petrol and diesel engines
- \* Outstanding engine cleanliness and sludge control

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Keep sealed in a cool, dry place.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water





## Granville Hypalube LX Mineral 10W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.9
Cold Cranking Viscosity	ASTM D4684	mPa.s		7000	
Total Base Number	ASTM D2896	mg KOH/g	10		12.12
Pour Point	ASTM D97	°c		-30	-33
HTHS Viscosity	ASTM D4683	mPa.s	3.5		
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			69.24
Density	ASTM D792	@ 15°C			0.869
Viscosity Index	ASTM D2270				147.777

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

