



## Granville Hypalube SL SS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

### Product Description

Granville Hypalube Semi Synthetic 5W/30 is a synthetic based engine oil designed to provide maximum protection for modern engines requiring a low viscosity oil. It is suitable for lean burn, multi-valve, injection, twin cam, turbo charged and Ford Zetec engines.

### Recommended for use by Granville for the following manufacturer's specifications

API: SL/CF  
ACEA: A1/B1



\* Image for illustrative purposes only.

### Product Benefits

- \* Ensures lubricant performance over extended drain intervals
- \* Excellent high & low temperature performance
- \* Outstanding fuel efficiency
- \* Effective environmental protection

### Product Usage

For engines where this specification lubricant is required.

### Directions for Use

As recommended by the engine manufacturer.

### Storage Instructions

Store upright and sealed in a cool, dry place out of the reach of children.

### Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Solubility	:	Insoluble in water
Percentage of Base Oil	:	More Than 80%
Percentage of Biodiesel	:	Nil

Size	Part No	Barcode
1 Litre	0427	5020618004271
5 Litre	0435	5020618004356
20 Litre	0262	5020618002628
199 Litre	0426	5020618004264





## Granville Hypalube SL SS 5W/30

1 Litre, 5 Litre, 20 Litre & 199 Litre

Test	Method	Unit	Min.	Max.	Typical
Kinematic Viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	9.3	<12.5	10.38
Cold Cranking Viscosity	ASTM D4684	mPa.s		6600	
Total Base Number	ASTM D2896	mg KOH/g	8		10.62
HTHS Viscosity	ASTM D4683	mPa.s	2.9	3.5	
NOACK Volatility	ASTM D5800	%		13	
Kinematic Viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s			62.95
Density	ASTM D792	@ 15°C			0.862
Pour Point	ASTM D97	°C		-35	

### Safety Precautions

Please see our latest EC Safety Data Sheets for details.

### Transport Classification

Please see our latest EC Safety Data Sheets for details.

