# **TECHNICAL DATA SHEET**



Product Code: 6124 Sector: Automotive (Passenger Car & LCV) Issue No: 3 Issue Date: 01/06/23

# TRIDENT PROFESSIONAL ENGINE OIL C3 5w40

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

#### **Application**

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a C3 5w40 viscosity targeting 'Pumpe Düse' PD Volkswagen Audi Group, GM and Mercedes Benz.

#### **Performance Profile**

ACEA C3 API SN, CF

#### Suitable for

BMW Longlife-04 (LL-04)
Chrysler MS-10725
Fiat 9.55535-T2, Fiat 9.55535-S2
Ford WSS-M2C917-A
General Motors GM dexos 2
GM-LL-B-025, GM-LL-A-025
Mercedes-Benz MB 229.52, MB 229.51,
MB 229.31, MB 226.5
Porsche A40, Porsche C40
PSA B71-2290 <2014
Renault RN0700 / RN0710
VW 502 00 / 505 01, VW 502 00 / 505 00
Asian manufacturers

#### **Features & Benefits**

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which reduces emissions and provides extended drain capability.
- Utilising mid SAPS technology protecting particulate filters and controlling soot build up.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

### **Typical Characteristics**

Density @ 15°C, g/ml 0.847 Kinematic Viscosity @ 100°C, cSt. 13.5 Flashpoint, °C >200

## **Technical & Health and Safety**

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS - Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer







