

Shell Helix Ultra Professional AJ-L 0W-30

Fully Synthetic Motor Oil - Tailored to meet engine manufacturer special requirements

• Designed to meet the demanding requirements of particular high-performance engines from Jaguar-Land Rover and those requiring ACEA C2

Proud Drivers Choose Shell Helix

Main Applications

 Shell Helix Ultra Professional AJ-L for diesel engines is approved against the technically challenging in-house technical requirements of the Jaguar Land Rover engineoil specification STJLR.03.5007

Specifications, Approvals & Recommendations

- API SN
- ACEA C2
- Jaguar Land Rover STJLR.03.5007
- To find the right Shell Helix product for your vehicles and equipment, please consult Shell LubeMatch at: http://lubematch.shell.com
- Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or technical helpdesks

Properties			Method	Shell Helix Ultra Professional AJ-L 0W-30
Kinematic Viscosity	@100°C	cSt	ASTM D445	9.80
Kinematic Viscosity	@40°C	cSt	ASTM D445	52.00
Viscosity Index			ASTM D2270	179
MRV	@-40°C	cP	ASTM D4684	14 400
Density	@15 [°] C	kg/m ³	ASTM D4052	833.5
Flash Point		٥C	ASTM D92	233
Pour Point		٥C	ASTM D97	-54

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on health and safety is available on the appropriate Safety Data Sheet (SDS) which can be obtained from http://epc.shell.com

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.